



Cut protection

KRYTECH 615

High risk - ISO D



CUT PROTECTION
LEVEL D

EN 388



4X43D

ISO 13997
20 N (2039 g)

Dexterity EN ISO
21420: 5/5

CATEGORY 2



High cut protection without any compromise on comfort and dexterity. Usable with touch screens.

SPECIFIC ADVANTAGES



Cut protection

- High cut protection without any compromise on comfort, dexterity and breathability. Usable with touch screens.



Comfort

- A seamless plaited glove for very good fit, dexterity and flexibility.



Durability

- Optimal durability that offers better productivity and optimizes your costs



Skin protection

- Free of harmful substances: OEKO-TEX® STANDARD 100



Suitable for touchscreen

- Can be used with touch devices & touch screen (thumb & index)



Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Washability

- Washable up to 3 times at 60°C , allowing to extend glove lifespan, reduce costs and waste.



Practical

- Cut level easy to identify thanks to the marking on the back of the glove.



Care for the environment

- 130 gr CO₂ of carbon footprint reduction (1)
- Recycled material in the glove: 25 %
- Recycled material in the liner: 27 %
- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

INDUSTRIES

- Automotive industry
- Construction industry:
Carpenters/Joiners
- Construction industry:
Metalworkers/Locksmiths
- Glass industry
- Mining industry

APPLICATIONS

- Strip cutting / Plasma strip cutting
- Handling sheet metal
- Metal working
- Installing steel structures
- Handling
- Handling glass sheets
- Maintenance with cut risk
- Mechanical maintenance
- Handling of thick metal sheets



Cut protection

KRYTECH 615

High risk - ISO D

LEGENDS

EN388		MECHANICAL HAZARDS	
		PERFORMANCE LEVELS (X = NOT TESTED)	
4	X	4	3 D
0-4	0-5	0-4	0-4 A-F P
		Impact protection (optional)	
		Cut resistance according to ISO 13997	
		Puncture resistance	
		Tear resistance	
		Blade cut resistance	
		Abrasion resistance	

PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE fibres
Gauge	13
Exterior finish	Ventilated back
Material	Polyurethane
Cuff characteristic	Knitted Cuff
Colour	Black, Grey
Length (cm)	24-30
Sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.0E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	2.9E+9 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton
-----------	---

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/04/18/0697
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

(1) Measurement based on life cycle analysis, carried out by Glimpact, an independent third party, according to the European PEF method adopted by European Commission, based a pair of cut D polyurethane gloves.

Edit 07/09/2026