Cut protection

KRYTECH 615

High risk - ISO D

High cut protection without any compromise on comfort and dexterity. Usable with touch screens.



CUT PROTECTION
LEVEL D

EN 388



4X43D

ISO 13997
20 N (2039 g)

Dexterity EN ISO
21420: 5/5

CATEGORY 2

CE

OEKO TEX®
STANDARD 100
CQ 979/3
IFTH

SPECIFIC ADVANTAGES

Cut protection

- High cut protection without any compromise on comfort, dexterity and breathability. Usable with touch screens.

Comfort

- A seamless plaited glove for very good fit, dexterity and flexibility.

Durability

- Optimal durability that offers better productivity and optimizes your costs

Skin protection

- Free of harmful substances: OEKO-TEX® STANDARD 100

Suitable for touchscreen

- Can be used with touch devices & touch screen (thumb & index)

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

Washability

- Washable up to 3 times at 60°C , allowing to extend glove lifespan, reduce costs and waste.

Practical

- Cut level easy to identify thanks to the marking on the back of the glove.

Care for the environment

- 130 gr CO_2 of carbon footprint reduction (1)
- Recycled material in the glove: 25 %
- Recycled material in the liner: 27 %
- Optimised individual packaging to limit plastic waste
- Recycled material in the packaging: 30 %

INDUSTRIES

- Automotive industry
- Construction industry: Carpenters/Joiners
- Construction industry: Metalworkers/Locksmiths
- Glass industry
- Mining industry

APPLICATIONS

- Strip cutting / Plasma strip cutting
- Handling sheet metal
- Metal working
- Installing steel structures
- Handling
- Handling glass sheets
- Maintenance with cut risk
- Mechanical maintenance
- Handling of thick metal sheets

Edit 29/10/2026

Cut protection

KRYTECH 615

High risk - ISO D

LEGENDS

EN388



MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

4	X	4	3	D	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 4: Abrasion resistance

PRODUCT DETAILS

Interior finish	Seamless textile support from HDPE fibres
Gauge	13
Exterior finish	Ventilated back
Material	Polyurethane
Cuff characteristic	Knitted Cuff
Colour	Black, Grey
Length (cm)	24-30
Sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.0E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	2.9E+9 Ω
**Life Cycle Analysis (kg CO2eq)	0.78

**Calculated according to the European PEF methodology (EF 3.1), in accordance with ISO 14040 and ISO 14044. Cradle-to-grave scope, excluding the use phase. LCA data extracted in September 2026. Calculated on the standard reference.

LOGISTIC DETAILS

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/04/18/0697
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

(1) Measurement based on life cycle analysis, carried out by Glimpact, an independent third party, according to the European PEF method adopted by European Commission, based a pair of cut D polyurethane gloves.

Edit 29/10/2026