Thermal protection

TEMPICE 780

Temperature to -10°C | Wet environments

100% PVC



CHEMICAL PROTECTION
TYPE B

EN 388
3221X

EN 374-1
Type B
KPT

EN 374-5

EN 511
121

Dexterity EN ISO 21420: 5/5

CATEGORY 3
CE
0334

SPECIFIC ADVANTAGES

Thermal protection

- PVC specially designed for use in extreme cold (-10°C) while preserving the flexibility of the glove

Durability

- Good resistance to oils, greases and hydrocarbons

Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

INDUSTRIES

- Logistics
- Food industry

APPLICATIONS

- Handling of liquids at low temperatures (water, oil, hydrocarbons, etc.)
- Food handling
- Maintenance and work in cold stores

Edit 30/10/2026

Thermal protection

TEMPICE 780

Temperature to -10°C | Wet environments

LEGENDS

EN388 — MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

3	2	2	1	X	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 0-4: Abrasion resistance

EN 511:2006 — COLD HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)

1	2	1
0-4	0-4	0/1

- 0/1: Water permeability
- 0-4: Contact cold resistance
- 0-4: Convective cold resistance

EN ISO 374-1 — CHEMICAL RISKS



TYPE B

K: Sodium hydroxide 40%
P: Hydrogen peroxide 30%
T: Formaldehyde 37%

EN ISO 374-5 — MICRO-ORGANISMS



Protection against bacteria and fungi

PRODUCT DETAILS

Interior finish	Jersey support, lined with woolen fleece
Exterior finish	Pebbled
Material	PVC
Colour	Orange
Length (cm)	30
Sizes	9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	1.7E+9 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	1.7E+11 Ω
**Life Cycle Analysis (kg CO2eq)	1.97

**Calculated according to the European PEF methodology (EF 3.1), in accordance with ISO 14040 and ISO 14044. Cradle-to-grave scope, excluding the use phase. LCA data extracted in September 2026. Calculated on the standard reference.

LOGISTIC DETAILS

Packaging	1 pair/bag 48 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/04/22/0794
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 30/10/2026