Chemical protection

ALTO 299

Prolonged contact (or immersion) | intermittent wear

Good mechanical performance for long-lasting chemical protection



CHEMICAL PROTECTION
TYPE A

EN 388
3121X

EN 374-1
Type A
AKLMPT

EN 374-5

Dexterity EN ISO 21420: 5/5

CATEGORY 3
CE
0334

SPECIFIC ADVANTAGES

Durability

- Longer service life and good impact protection, due to the thickness of the material

INDUSTRIES

- Construction industry: Heating engineers/Plumbers
- Metallurgy

APPLICATIONS

- Emprying and cleaning septic tanks
- Maintenance in wet environments (water, oil, greases, hydrocarbons)

Edit 01/11/2026

Chemical protection

ALTO 299

Prolonged contact (or immersion) | intermittent wear

LEGENDS

EN388

MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT TESTED)

3	1	2	1	X	
0-4	0-5	0-4	0-4	A-F	P

- P: Impact protection (optional)
- A-F: Cut resistance according to ISO 13997
- 0-4: Puncture resistance
- 0-4: Tear resistance
- 0-5: Blade cut resistance
- 3: Abrasion resistance

EN ISO 374-1

TYPE A

CHEMICAL RISKS

A: Methanol
K: Sodium hydroxide 40%
L: Sulphuric acid 96%
M: Nitric acid 65%
P: Hydrogen peroxide 30%
T: Formaldehyde 37%

EN ISO 374-5

MICRO-ORGANISMS

Protection against bacteria and fungi

LOGISTIC DETAILS

Packaging	1 pair/bag 5 pairs/bag 50 pairs/carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/09/18/2001
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Edit 01/11/2026