ULTRANEO 339

Prolonged contact (or immersion) | continous wear

Comfort and high-level chemical protection



CHEMICAL PROTECTION **TYPE A**

EN388



EN ISO 374-1



TYPE A **ABCJLMNS**

CATEGORY 3



0334

SPECIFIC ADVANTAGES



Thermal protection

• Thermal insulation from the cotton-knit lining for handling hot liquids



Durability

• Excellent mechanical resistance and longer service life, due to the textile support and the thickness of the glove



Productivity

Pebbled embossing, for better grip on wet and slippery objects



Skin protection

• Superior chemical resistance against acids and alkalis, such as concentrated hydrofluoric acid, oils, and greases, due to its 100% neoprene multi-layer construction



EN407

X1XXXX

Guaranteed quality

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting

INDUSTRIES

- Mechanical industry
- Chemical industry

APPLICATIONS

- Surface treatment of metals (acids)
- Handling and transporting drums of chemical products
- Handling on alkylation units
- Hot, petrochemical product sampling
- Resin-working
- Site pollution control

Edit 04/10/2023

ULTRANEO 339

Prolonged contact (or immersion) | continous wear

LEGENDS

EN388

MECHANICAL HAZARDS

PERFORMANCE LEVELS (X = NOT


Impact protection (optional) Cut resistance according to ISO 13997 Puncture resistance Tear resistance Blade cut resistance Abrasion resistance

EN407

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT



EN ISO 374-1



A: Methanol

- **CHEMICAL RISKS** B: Acetone
- C: Acetonitrile
- J: n-Heptane
- L: Sulphuric acid 96%
- M: Nitric acid 65%
- N: Acetic acid 99%
- S: Hydrofluoric acid 40%

PRODUCT DETAILS

Interior finish	Textile support
Exterior finish	Pebbled
Material	Polychloroprene
Cuff characteristic	Feston Cuff
Colour.s	Black
Length (cm)	36
Thickness (mm)	1.6
European sizes	9 10
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	2.9E+11 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	1.2E+11 Ω

LOGISTIC DETAILS

Packaging	1 pair/bag 6 pairs/carton
	o pano, carton

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation no 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/18/2912 updated 01-11/10/2021
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

