# **ULTRANITRIL 485**

Frequent contact | intermittent wear

### Good sensitivity for standard chemical protection

CHEMICAL PROTECTION **TYPE B** 

EN388



3101X

**JKOPT** 

**CAT.CATEGORY 3** 

0334



ISO 18889

EN ISO 374-1



DEXTERITY

**VIRUS** 

EN ISO 374-5

EN 420: 5/5

## SPECIFIC ADVANTAGES



### Comfort

• Excellent dexterity, due to the suppleness of the glove



#### **Productivity**

Good grip on slippery objects, due to the embossed texture



### **Guaranteed quality**

• Silicone free to prevent traces, defects on metal sheet and glass prior to painting

### **INDUSTRIES**

- Automotive/mechanical industry
- Chemical industry
- Other industries
- Agriculture sector

### **APPLICATIONS**

- Spray mixtures preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Manufacture and application of paints and varnishes
- Application of phytosanitary products
- Maintenance
- Timber treatment and finishing

Edit 30/06/2023

## **ULTRANITRIL 485**

Frequent contact | intermittent wear

## **LEGENDS**

**FN388** 

**MECHANICAL HAZARDS** 



PERFORMANCE LEVELS (X = NOT

Impact protection (optional) Cut resistance according to ISO 13997 Puncture resistance Tear resistance

#### EN ISO 374-1

#### **CHEMICAL RISKS**

Blade cut resistance



TYPE B

Abrasion resistance

J: n-Heptane

- K: Sodium hydroxide 40%
- O: Ammonia 25%
- P: Hydrogen peroxide 30%
- T: Formaldehyde 37%



#### PROTECTION FROM PESTICIDES

G2: Diluted & concentrated pesticides / Mechanical risk

ISO 18889

#### EN ISO 374-5



MICRO-ORGANISMS

Protection against bacteria, fungi and

## PRODUCT DETAILS

| Interior finish     | Flocked          |
|---------------------|------------------|
| Exterior finish     | Embossed texture |
| Material            | Nitrile          |
| Cuff characteristic | Straight cuff    |
| Colour.s            | Green            |
| Length (cm)         | 31               |
| Thickness (mm)      | 0.34             |
| European sizes      | 7 8 9 10         |

## LOGISTIC DETAILS

| Packaging 12 pairs/bag 72 pairs/carton |
|--|
|--|

### **LEGISLATION**

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE certificate CE type examination certificate: type 0075/014/162/10/18/2079
- Issued by the notified body nr: 0075 CTC 4, rue Hermann Frenkel 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 Asqual 14 rue des Reculettes -75013 Paris -France

Edit 30/06/2023