CHEMZOIL NL-339

Comfort and high-level chemical protection

SPECIFIC ADVANTAGES

Thermal protection

• Thermal insulation from the cotton-knit lining for handling hot liquids



• Excellent mechanical resistance and longer service life, due to the textile support and the thickness of the glove

Productivity

Pebbled embossing, for better grip on wet and slippery objects



• Superior chemical resistance against acids and alkalis, such as concentrated hydrofluoric acid, oils, and greases, due to its 100% neoprene multi-layer construction

EN388



EN407

X1XXXX



INDUSTRIES

- Mechanical industry
- Chemical industry

APPLICATIONS

- Handling and transporting drums of chemical products
- Handling on alkylation units
- Hot, petrochemical product sampling
- Resin and adhesive manufacturing
- Site pollution control
- Surface treatment of metals (acids)



CHEMZOIL NL-339


LEGENDS

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT




FN407

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT



PRODUCT DETAILS

Interior finish	Textile support
Exterior finish	Pebbled
Material	Neoprene
Colors of the gloves	Black
Length (cm)	36
Thickness (mm)	1.35

LOGISTIC DETAILS

Packaging	6 pairs/carton
-----------	----------------

LEGISLATION

- This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.
- This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0072/014/162/10/01/0144
- Issued by the notified body nr: 0072 I.F.T.H. Av. Guy de Collongue F-69134 **ECULLY CEDEX**

