



Chemical protection

ULTRANITRIL 480

Prolonged contact (or immersion) | short wear

Ultra-long chemical protection



KEMISKT SKYDD
TYP A

EN388



4102X

EN ISO 374-1



TYP A
AJKOPT

EN ISO 374-5



DEXTERITY

EN 420:
5/5

CAT.CATEGORY 3



0334



G2
ISO 18889



SPECIFIKA FÖRDELAR



Durability

- Longer service life: excellent mechanical resistance (abrasion, perforation)



Productivity

- Good grip on slippery objects, due to the embossed texture



Skin protection

- Excellent protection during intensive handling of high-risk chemical products



Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting

INDUSTRIER

- Automotive/mechanical industry
- Chemical industry
- Other industries
- Agriculture sector

APPLIKATIONER

- Spray mixtures preparation
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Handling drums of chemical products
- Application of pesticides
- Cleaning of printing-press rollers
- Maintenance
- Timber treatment and finishing



Chemical protection

ULTRANITRIL 480

Prolonged contact (or immersion) | short wear

LEGENDER

| | |
|-----------------------|---|
| EN388 | MECHANICAL HAZARDS |
| | PERFORMANCE LEVELS (X = NOT TESTED) |
| 4 1 0 2 X | |
| 0-4 0-5 0-4 0-4 A-F P | |
| | Impact protection (optional) |
| | Cut resistance according to ISO 13997 |
| | Puncture resistance |
| | Tear resistance |
| | Blade cut resistance |
| | Abrasion resistance |
| EN ISO 374-1 | CHEMICAL RISKS |
| | A: Methanol |
| TYP A | J: n-Heptane |
| | K: Sodium hydroxide 40% |
| | O: Ammonia 25% |
| | P: Hydrogen peroxide 30% |
| | T: Formaldehyde 37% |
| | PROTECTION FROM PESTICIDES |
| G2 | G2: Diluted & concentrated pesticides / Mechanical risk |
| ISO 18889 | |
| EN ISO 374-5 | MICRO-ORGANISMS |
| | Protection against bacteria and fungi |
| | FOOD CONTACT |
| | French decree of 05/08/2020 |

PRODUKTINFORMATION

| | |
|---------------------|------------------|
| Interior finish | Chlorinated |
| Exterior finish | Embossed texture |
| Material | Nitrile |
| Cuff characteristic | Straight cuff |
| Colour.s | Green |
| Length (cm) | 46 |
| Thickness (mm) | 0.55 |
| European sizes | 7 8 9 10 11 |

LOGISTISKA DETALJER

| | |
|-----------|-------------------------------|
| Packaging | 1 pair/bag 12 pairs/carton |
|-----------|-------------------------------|

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/16206/18/1069
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Redigera 30/06/2023