

KRYTECH 576

High-performance protection for intricate handling in reasonably clean environments



SKÄRSKYDD
NIVÅ D

EN388



4X42D

CAT.CATEGORY 2



DEXTERITY

EN 420:
5/5

SPECIFIKA FÖRDELAR



Cut protection

- Optimal cut resistance: level 5 (ANSI Cut 4)



Comfort

- Excellent dexterity due to the precise fit
- Added comfort and flexibility



Skin protection

- Contains traces of DMF in compliance with occupational exposure limits


INDUSTRIER

- Automotive/mechanical industry
- Local Authorities (Technical Maintenance)
- Construction Industry (Roofers/Tilers/Glazers)
- Plastics industry

APPLIKATIONER

- Post-injection material removal
- Maintenance work with risk of cuts
- Handling and fitting windows
- Assembly of thin metal sheets
- Finishing sharp parts
- Handling metal parts

LEGENDER

EN388		MECHANICAL HAZARDS	
		PERFORMANCE LEVELS (X = NOT TESTED)	
4	X	4	2 D
0-4	0-5	0-4	0-4 A-F P
			Impact protection (optional)
			Cut resistance according to ISO 13997
			Puncture resistance
			Tear resistance
			Blade cut resistance
			Abrasion resistance

PRODUKTINFORMATION

Interior finish	Seamless textile support from HDPE fibres
Gauge	13
Exterior finish	Ventilated back
Material	Polyurethane
Cuff characteristic	Knitted Cuff
Colour.s	Grey
Length (cm)	22-27

LOGISTISKA DETALJER

Packaging	1 pair/bag 12 pairs/bag 96 pairs/carton
-----------	---

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/01/19/0137
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE