

Ultra-high performance chemical protection



EN388



3112

EN ISO 374-5



SPECIFIKA FÖRDELAR



Productivity

- Good grip due to the embossed texture



Skin protection



- Broad chemical resistance (acids, aliphatic solvents, solvent mixtures), increased by the thickness of the material



Practical

- Easy to pull on and off, due to chlorinated interior

LEGENDER

| | |
|--|--|
| EN388 | MECHANICAL HAZARDS |
|  | |
| 3 1 1 2 | PERFORMANCE LEVELS (X = NOT TESTED) |
| 0-4 0-5 0-4 0-4 | A-F P |
| | Impact protection (optional) |
| | Cut resistance according to ISO 13997 |
| | Puncture resistance |
| | Tear resistance |
| | Blade cut resistance |
| | Abrasion resistance |
| EN ISO 374-5 | MICRO-ORGANISMS |
|  | Protection against bacteria and fungi |

PRODUKTINFORMATION

| | |
|----------------------|------------------|
| Interior finish | Chlorinated |
| Exterior finish | Embossed texture |
| Material | Neoprene |
| Cuff characteristic | Straight cuff |
| Colors of the gloves | Black |

LOGISTISKA DETALJER

| | |
|-----------|---------------------------------|
| Packaging | 12 pairs/box 72 pairs/carton |
|-----------|---------------------------------|

LEGISLATION

- This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.
- This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).