CHEMZOIL NL-339

Comfort and high-level chemical protection

SPECIFIKA FÖRDELAR

Thermal protection

• Thermal insulation from the cotton-knit lining for handling hot liquids



Durability

• Excellent mechanical resistance and longer service life, due to the textile support and the thickness of the glove



Productivity

Pebbled embossing, for better grip on wet and slippery objects



Skin protection

• Superior chemical resistance against acids and alkalis, such as concentrated hydrofluoric acid, oils, and greases, due to its 100% neoprene multi-layer construction

EN388



EN407

X1XXXX



0334

INDUSTRIER

- Mechanical industry
- Chemical industry

APPLIKATIONER

- Handling and transporting drums of chemical products
- Handling on alkylation units
- Hot, petrochemical product sampling
- Resin and adhesive manufacturing
- Site pollution control
- Surface treatment of metals (acids)



CHEMZOIL NL-339


LEGENDER

EN388

MECHANICAL HAZARDS



PERFORMANCE LEVELS (X = NOT TESTED)




FN407

THERMAL RISKS (HEAT AND FIRE)



PERFORMANCE LEVELS (X = NOT TESTED)



PRODUKTINFORMATION

Interior finish	Textile support
Exterior finish	Pebbled
Material	Neoprene
Colors of the gloves	Black
Length (cm)	36
Thickness (mm)	1.35

LOGISTISKA DETALJER

Packaging	6 pairs/carton
-----------	----------------

LEGISLATION

- This product is not classified as hazardous according to the directive 1999/45/EC of the European Parliament and of the Council.
- $^{\circ}$ This product does not contain any substances of very high concern according to the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0072/014/162/10/01/0144
- Issued by the notified body nr: 0072 I.F.T.H. Av. Guy de Collongue F-69134 ECULLY CEDEX

