



Cut protection

KRYTECH 582

High risk - ISO D



GRIP & PROOF
TECHNOLOGY

SKÄRSKYDD
NIVÅ D



CAT.CATEGORY 2



ISO 13997:

18 N

DEXTERITY

EN 420:
5/5



Special Grip&Proof nitrile coating provides better liquidproofness and grip in oily situations

SPECIFIKA FÖRDELAR



Cut protection

- Optimal cut resistance



Durability

- Excellent abrasion resistance increases glove lifetime



Productivity

- Grip and Proof coating ensures an excellent grip in oily environment. It also reduces muscle strain and boost productivity



Skin protection

- Free of harmful substances: DMF Free



Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Washability

- Washable up to 5 times at 60°C without any alteration on performances* allowing to extend glove lifespan, reduce costs and waste.



Practical

- Cut level easy to identify thanks to the marking on the back of the glove.

INDUSTRIER

- Automotive/mechanical industry
- Mechanical industry
- Glass industry

APPLIKATIONER

- Handling glass sheets
- Cutting and stamping metal
- Assembly of thin metal sheets
- Finishing sharp parts
- Handling metal parts
- Metal rolling, stamping and assembly
- Metal working

Redigera 30/06/2023

MAPA SAS capital de 35.000.010 €
420, rue d'Estienne d'Orves
92705 Colombes Cedex France
RCS Nanterre 314 307 720

mapa-pro.com

MAPA
PROFESSIONAL



Cut protection

KRYTECH 582

High risk - ISO D

LEGENDER

EN388		MECHANICAL HAZARDS	
PERFORMANCE LEVELS (X = NOT TESTED)			
4	X	4	3 D
0-4	0-5	0-4	0-4 A-F P
			Impact protection (optional)
			Cut resistance according to ISO 13997
			Puncture resistance
			Tear resistance
			Blade cut resistance
			Abrasion resistance

PRODUKTINFORMATION

Interior finish	Seamless textile support from HDPE fibres
Gauge	13
Exterior finish	Non-slip grip
Material	Nitrile GRIP&PROOF coating
Cuff characteristic	Knitted Cuff
Colour.s	Black Blue
European sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	5.9E+9 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	4.8E+10 Ω

LOGISTISKA DETALJER

Packaging	1 pair/bag 12 pairs/bag 48 pairs/carton
-----------	-----------------------------------------------

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/12/18/2873
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE

* Testerna utfördes med oanvända handskar (dvs. i nytt tillstånd) vilket skiljer sig från verkligheten ute på fältet.

Redigera 30/06/2023