



Chemical protection

ULTRANITRIL 492

Frequent contact | intermittent wear



KEMISKT SKYDD
TYP A

EN388



3101X

EN ISO 374-1



TYP A
AJKOPT

EN ISO 374-5



VIRUS

CAT.CATEGORY 3

DEXTERITY



G2
ISO 18889



0334

EN 420:
5/5

Good mechanical resistance and long-lasting chemical protection

SPECIFIKA FÖRDELAR



Comfort

- Dexterity and comfort, due to the anatomical shape and the quality of the flock-lining



Durability

- Longer service life: excellent mechanical resistance (abrasion, perforation)



Guaranteed quality

- Silicone free to prevent traces, defects on metal sheet and glass prior to painting



Additional benefits

- Available in vending machine packaging

INDUSTRIER

- Automotive/mechanical industry
- Local Authorities (Cleaning)
- Local Authorities (Parks and Public Spaces)
- Construction Industry (Masons / Plasterers)
- Construction Industry (Carpenters/Joiners)
- Agriculture sector

APPLIKATIONER

- Spray mixtures preparation
- Pesticides handling
- Tank filling
- Application & spreading of pesticides
- Pesticides waste management
- Treatment equipment cleaning
- Handling oils, solvents, detergents
- Preparing coatings, varnishes
- Handling PVC-based glues
- Handling aggressive chemical products

Redigera 30/06/2023

MAPA SAS capital de 35.000.010 €
420, rue d'Estienne d'Orves
92705 Colombes Cedex France
RCS Nanterre 314 307 720

mapa-pro.com

MAPA
PROFESSIONAL



Chemical protection

ULTRANITRIL 492

Frequent contact | intermittent wear

LEGENDER

EN388	MECHANICAL HAZARDS
	PERFORMANCE LEVELS (X = NOT TESTED)
3 1 0 1 X	
0-4 0-5 0-4 0-4 A-F P	
	Impact protection (optional)
	Cut resistance according to ISO 13997
	Puncture resistance
	Tear resistance
	Blade cut resistance
	Abrasion resistance
EN ISO 374-1	CHEMICAL RISKS
	A: Methanol
TYP A	J: n-Heptane
	K: Sodium hydroxide 40%
	O: Ammonia 25%
	P: Hydrogen peroxide 30%
	T: Formaldehyde 37%
	PROTECTION FROM PESTICIDES
G2	G2: Diluted & concentrated pesticides / Mechanical risk
ISO 18889	
EN ISO 374-5	MICRO-ORGANISMS
	Protection against bacteria, fungi and virus
VIRUS	

PRODUKTINFORMATION

Interior finish	Flocked
Exterior finish	Embossed texture
Material	Nitrile
Cuff characteristic	Straight cuff
Colour.s	Green
Length (cm)	32
Thickness (mm)	0.38
European sizes	6 7 8 9 10 11
Surface resistance according to EN1149-1 (Value in palm area at 25% relative humidity)	6.4E+10 Ω
Vertical resistance according to EN1149-2 (Value in palm area at 25% relative humidity)	5.8E+9 Ω

LOGISTISKA DETALJER

Packaging	1 pair/bag 10 pairs/bag 100 pairs/carton
-----------	------------------------------------------------

LEGISLATION

- This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council.
- This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).
- UE type certificate or CE type examination certificate: 0075/014/162/08/18/1631
- Issued by the notified body nr: 0075 CTC - 4, rue Hermann Frenkel - 69367 Lyon Cedex 07- FRANCE
- Quality assurance certificat: 0334 - Asqual 14 rue des Reculettes -75013 Paris - France

Redigera 30/06/2023